

WT-1 JUMPER	DTE Receive Distance
SELECT DESIRED OPTION:	
1 - 2*	0' - 85' * <input type="checkbox"/>
3 - 4	85' - 375' <input type="checkbox"/>
5 - 6	375' - 655' <input type="checkbox"/>

S2	Transmit (Artificial Line)
SELECT DESIRED OPTION:	
15dB	0 - 1000' twisted copper <input type="checkbox"/>
7.5dB *	1000' - 2000' twisted copper * <input type="checkbox"/>
0dB	2000' - 3000' twisted copper or local DS3 mux, radio, or other equipment requiring DSX level <input type="checkbox"/>

WT-2 JUMPER	DTE Transmit Distance
SELECT DESIRED OPTION:	
1 - 2*	0' - 85' * <input type="checkbox"/>
3 - 4	85' - 375' <input type="checkbox"/>
5 - 6	375' - 655' <input type="checkbox"/>

S1	Critical Circuitry Power
SELECT DESIRED OPTION:	
SP *	Span power * <input type="checkbox"/>
WL	Local Power Wet Loop (CSU applies sealing current) <input type="checkbox"/>
DL	Local Power Dry Loop (Loop any sealing current) <input type="checkbox"/>

- NOTES:**
- * = These are the factory defaults and are those most commonly used in the field.
 - For additional installation information, refer to manual Part No. 880-500497-001.
 - FCC Reg: GIC472-16545-DE-N
FIC: O4DU9-B
 - Telco jack: DA-15 or wire-wrap

